
Order Online at www.hafele.co.uk



- A Four sided column, slotted on two sides
- For use with all brackets except U-brackets
- Plastic coated steel



- B Four sided column, slotted on four sides
- For use with all brackets except U-brackets
- Plastic coated steel



- C Four sided column, double slotted on two sides
- For use with all brackets
- Plastic coated steel



Plug fits into 30 x 30 mm columns

Plastic



- E Column fastening materials
- For fixing four sided 30 x 30 mm columns


Base unit and ceiling pin clamp with centering pin and plug

Dimensions amended, drawings extended to show bottom of columi

25.5

25

22



A Four sided column, slotted on two sides

- 3			
	Length	White (RAL 9003)	Silver coloured (RAL 9006)
	2600 mm	772.12.269	770.12.226
	3000 mm	772.12.303	770.12.230

Packing: 1 pc

B Four sided column, slotted on four sides

Length	White (RAL 9003)	Silver coloured (RAL 9006)
2600 mm	772.14.263	770.14.226
3000 mm	772.14.307	770.14.230

Packing: 1 pc

Feet for 30 x 30 mm double slotted columns are shown on page 18, item B

C Four sided column, double slotted on two sides

Length	White (RAL 9003)	Silver coloured (RAL 9006)		
2600 mm	772.11.262	770.11.226		
3000 mm	772.11.306	770.11.230		
Packing: 1 pc				

D Trim cap

sap				
Finish	White (RAL 9003)	Silver coloured (RAL 9006)		
Cat. No.	772.91.975	770.91.297		

Packing: 1 pc





E Column fastening materials

Cat. No. 772.25.015

Packing: 1 pc

Section