

Order Online at www.hafele.co.uk





- For use with all brackets
- Double slotted on either side, for use with column support rail
- Plastic coated steel



770.16.229

Silver coloured (RAL 9006)

770.16.280

770.16.281

770.16.282


Silver coloured (RAL 9006)

770.16.290

770.16.291

A Four sided column, double slotted on two sides White (RAL 9003) Silver coloured (RAL 9006) Length 1315 mm 772.16.713 770.16.213 2115 mm 772.16.721 770.16.221 2515 mm 772.16.725 770.16.225

2915 mm Packing: 1 pc





B Foot, 30 mm

- For use with 30 x 30 mm double slotted column and 60 x 30 mm columns
- With adjusting screws, adjustable +40 mm
- Plastic coated steel



White (RAL 9003)

772.16.780

772.16.781

772.16.782

White (RAL 9003)

772.16.790

772.16.791

-+-

772.16.729

500 mm Packing: 1 pc


625 mm

1000 mm

Packing: 1 pc

350 mm

400 mm



i.s	
Effective length 595/970 mm	
Length over engagement hooks 621/996 mm	
Centres 625/1000 mm	

C Column support rail

- For use with 60 x 30 mm columns
- Safety clip included
- Plastic coated steel

D Safety lock screw set

- For use with mobile shelving system
- M8 x 50 mm with nut
- Galvanized steel




D Safety lock screw set

Cat. No.		770.16.999
	Packing: 1 set (10 ncs)	



- E Gondola head frame
- Double slotted on two sides
- 30 x 30 x 2 mm tube
- Plastic coated steel
- Order connecting bracket shown on page
- 22, item D separately



E Insertable gondola head frame

Centres	White (RAL 9003)	Silver coloured (RAL 9006)	
625 mm	772.21.762	770.21.262	

Packing: 1 pc