



A Dry diamond core

Manufactured in the UK

- Combination of superior design and high quality manufacture
- Ideally suited to lightweight building materials, ordinary facing brickwork and blockwork up to 10n/mm²
- Dry diamonds are designed to give rapid, clean service entries with virtually no making good required
- Virtually no "break out" damage
- **Order accessories separately**, items **B-F**
- **Please note: Power tools of over 900W with a slipping clutch are required**

Ø x length	Cat. No.
22 x 300 mm	001.67.971
38 x 150 mm	001.67.974
48 x 150 mm	001.67.975
52 x 150 mm	001.67.976
65 x 150 mm	001.67.977
107 x 150 mm	001.67.980
117 x 150 mm	001.67.981
127 x 150 mm	001.67.982
152 x 150 mm	001.67.983

Order qty: 1 pc

Item A.
 Item added

Manufactured in the UK

B Dry diamond adaptor, 70 mm 1/2 BSP to Hex

- For use with dry diamond cores

	Cat. No.
70 mm 1/2 BSP to Hex	001.67.991

Order qty: 1 pc

Manufactured in the UK

C Dry diamond adaptor, 115 mm 1/2 BSP to SDS

- For use with dry diamond cores

	Cat. No.
115 mm 1/2 BSP to SDS	001.67.992

Order qty: 1 pc



Manufactured in the UK

D Dry diamond adaptor, A taper drill

- For use with dry diamond cores

	Cat. No.
A taper drill	001.67.993

Order qty: 1 pc



Manufactured in the UK

E Dry diamond adaptor, guide rod

- For use with dry diamond core

	Cat. No.
Guide rod	001.67.994

Order qty: 1 pc

Manufactured in the UK

F Dry diamond adaptor, 200mm 1/2 BSP extension

- For use with dry diamond cores

	Cat. No.
200 mm 1/2 BSP extension	001.67.995

Order qty: 1 pc

TCH-FF 2010, HUK. Dimensional data not binding. We reserve the right to alter specifications without notice.