



A Cloth belt, 100 x 610 mm

- For power sanding standard woodwork
- Full resin bonding maximises life for machine sanding operations
- Rigid cotton cloth, tear resistant
- Closed coat grit configuration for high stock removal and high quality surface finish
- Maroon aluminium oxide resin bonded with durable cotton cloth backing

Grit grade	Cat. No.
40	005.33.080
60	005.33.081
80	005.33.082
100	005.33.083
120	005.33.084
150	005.33.085
180	005.33.086
240	005.33.087

Order qty: Multiples of 10 pcs



B Cloth belt, 100 x 915 mm

- For power sanding heavy duty metalwork
- For wet and dry grinding applications
- Full resin bonding maximises life for machine sanding operations
- Rigid polyester cloth provides high resistance to tearing in high stock removal machine operations
- Semi-open coat grit configuration for high stock removal and high quality surface finish
- Maroon aluminium oxide resin bonded on polyester backing cloth

Grit grade	Cat. No.
36	005.33.070
40	005.33.071
60	005.33.072
80	005.33.073
120	005.33.074

Order qty: Multiples of 10 pcs

- Steel wool shown on page 89




C Sanding strip, 70 x 125 mm

- Velcro back for use with sanding block **E**
- For power and hand sanding
- For paint, plaster, filters, particle boards and softwoods
- Special Progressive Bond™ improves flexibility and resistance to grit shredding
- Aggressive abrasive for the coarse grades gives long life and flexibility for when used on contoured surfaces
- Exclusive specially reinforced paper provides superior grain support
- Maroon aluminium oxide

Grit grade	Cat. No.
80	005.33.090
120	005.33.091

Order qty: Multiples of 50 pcs



D Q Silver sanding strip, 70 x 125 mm

- Velcro back for use with sanding block **E**
- For power and hand sanding, for metal, hardwood and composites
- Special Progressive Bond™ improves flexibility and resistance to grit shredding
- Optimal aggressivity to achieve fast and efficient stock removal
- High heat endurance and tough in down-to-metal sanding operations
- Calcium stearate coating minimises clogging and loading
- Flexible latex backing excellent for contour sanding
- Grey aluminium oxide

Grit	Cat. No.
80	005.58.090
120	005.58.092
150	005.58.093
180	005.58.094
240	005.58.096
320	005.58.097

Order qty: Multiples of 100 pcs

E Sanding block

- For use with velcro backed sanding strips, items **C** and **D**
- Black gel foam

Size	Cat. No.
70 x 125 mm	005.33.120

Order qty: 1 pc



F Sanding block

- Rubber

Size	Cat. No.
67 x 123 mm	005.33.110

Order qty: 1 pc




G Sofflex abrasive roll

- Roll is divided into 200 perforated sheets, 115 x 125 mm
- A-weight paper specially impregnated with latex
- Flexible sponge backing reduces over sanding
- Special stearate coating, highly resistant to clogging
- Yellow aluminium oxide grit, fast denibbing

Grit	Cat. No.
180	005.58.130
240	005.58.131
320	005.58.132
400	005.58.133
500	005.58.134

Order qty: 1 roll



H Soft foam sanding pad

- 120 x 98 x 13 mm
- For denibbing applications
- Lightweight, excellent for sanding contoured surfaces
- Grey aluminium oxide

Grit	Cat. No.
Fine	005.58.300
Medium	005.58.301
Coarse	005.58.302

Order qty: 1 pc