

# A Silirub MA silicone marble and stone sealant

- A high-quality neutral, joint sealant based on silicones
- Very easy application
- Permanent colour, UV-resistant
- · Stays elastic after curing
- Does not cause staining on porous surfaces such as marble, granite or blue stone
- Contains fungicide for sanitary applications
- For all glazing jobs
- Cladding of facades of marble, granite and other natural stones
- 310 ml tube
- Gun is shown on page 94

Colour	Cat. No.
Clear	003.50.018
White	003.50.019
Travertine	003.50.021
Black	003.50.022

Order qty: 1 pc



## C Silicone sealant, fire retardant

- Fire rated neutral cure silicone sealant for joints which require a highly elastic sealant (movement capacity of up to 50%)
- Excellent adhesion to a wide range of building materials
- Suitable for interior and exterior applications
- Fire rating of up to 4 hours with normal backing material
- Tested to BS476 part 20/22
- 310 ml tube
- Gun is shown on page 94

Colour	Cat. No.
White	003.50.020

Order qty: 1 pc



## **E** Expanding foam, fire retardant

- Fire rated PU foam in an aerosol can
- It is fast curing and suitable for the complete filling of larger joints
- Expands in the joint to about twice its original volume
- Excellent adhesion to a wide range of building materials
- Outstanding insulation and soundproofing characteristics
- Suitable for interior and exterior applications
- Fire rating of up to 227 minutes
- Tested to BS 476 part 20/22
- 750 ml can

Colour	Cat. No.
White	003.52.110

Order qty: 1 pc



#### B Silicone sealant for glass

- Silicone sealant for all glass constructions
- Specially developed for the manufacturing of glass aquariums
- Excellent adhesion on dry, dust and grease free glass plates
- Use by preference plates of sufficient thickness, eventually reinforced with ribs
- Resists temperatures between -60°C to +200°C
- 310 ml tube

Consumables

• Gun is shown on page 94

Colour	Cat. No.
Clear	003.51.132

Order qty: 1 pc



### D Acrylic sealant, fire retardant

- Water based acrylic sealant and crack filler
- Paintable and remains flexible
- Intumescent in a fire situation
- Excellent adhesion to all porous surfaces
- Suitable for interior joints with low or medium movement (movement capacity of up to 20%)
- Fire rating of up to 4 hours with normal backing material
- Tested to BS476 part 20/22
- 310 ml tube
- Gun is shown on page 94

Colour	Cat. No.
White	003.50.080

Order qty: 1 pc