



A Double locking cylinder rim night latch

- Operation: Key from outside. Key lockable lever handle from inside
- Case: Standard or narrow stile
- Latchbolt: Automatically deadlocks on closing door
- Reverse turn of key deadlocks inside handle
- Bolt may be held in withdrawn position by snib
- Keys: 3 no. included
- **Standard:** Case size 90 mm, backset 60 mm
- **Narrow stile:** Case size 70 mm, backset 40 mm
- Fixing screws and instructions included

Case/cylinder finish	Cat. No.
Standard case	
Polished brass/pol. brass	911.23.213
Satin nickel/satin chrome	911.23.214
Pol. chrome/satin chrome	911.23.266
Narrow stile case	
Polished brass/pol. brass	911.23.215
Satin nickel/satin chrome	911.23.216
Pol. chrome/satin chrome	911.23.267

Order qty: 1 pc



B Rim night latch

- Operation: Key from outside. Lever from inside
- Case: Standard or narrow stile
- Latchbolt: Deadlock from outside by key
- Push button dead locks inside handle
- Bolt may be held in withdrawn position by snib
- Easily opened from inside in case of emergency
- Keys: 3 no. included
- **Standard:** Case size 90 mm, backset 60 mm
- **Narrow stile:** Case size 70 mm, backset 40 mm
- Fixing screws and instructions included

Case/cylinder finish	Cat. No.
Standard case	
Polished brass/pol. brass	911.23.217
Grey/satin chrome	911.23.218
Narrow stile case	
Polished brass/pol. brass	911.23.219
Grey/satin chrome	911.23.220

Order qty: 1 pc

DBB lock mortice jig

- Use with a drill with 2,000-3,000 rpm with hammer action off and a 12.7 mm chuck
- Max. door thickness (standard housing): 55 mm
- Screw-on design carbide tipped mortice wood cutters
- Cuts lock forend as well as lock body
- Self-centring action
- Achieves an accurate depth of cut to hardwood and softwood doors



C DBB mortice jig

- Suitable for all lock and latch cases. Cuts a mortice for body and faceplate
- Also for tubular latches, rack bolts and concealed door closers when used in conjunction with plunging cutters. For details see **Section 4 of The Complete Häfele for Architectural Ironmongery**
- Self-centring mortice jig with precision carbide tipped cutters complete with plastic carry case and instructions
- Vertical guides, height and depth stops mean you cannot over run the cut area
- Comprises: Mortice jig, Standard screw-on shaft: 220 mm length (for locks up to 100 mm deep), 1x Ø 19.0 mm, 1x Ø 22.2 mm and 1x Ø 25.4 mm carbide tipped cutter, Instruction booklet, 1x Allen key

	Cat. No.
DBB mortice jig	001.67.700

Order qty: 1 pc

D Wood cutter

- Increased cutting speed and longevity of sharpness retention
- Simplified screw-on 'anti-lock' design enables the cutter to be released quickly using a spanner (inc. with DBB mortice jig)
- Carbide tipped

Cutting Ø	Cutter reference	Cat. No.
Ø 16.2 mm	CWB16	001.67.842
Ø 17.5 mm	CWB18	001.67.843
Ø 19 mm	CWB19	001.67.844
Ø 20 mm	CWB20	001.67.845
Ø 20.6 mm	CWB21	001.67.846
Ø 22.2 mm	CWB22	001.67.847
Ø 23.0 mm	CWB23	001.67.848
Ø 23.8 mm	CWB24	001.67.849
Ø 25.4 mm	CWB25	001.67.850
Ø 27 mm	CWB27	001.67.851
Ø 28.6 mm	CWB29	001.67.852
Ø 31.8 mm	CWB32	001.67.853

Order qty: 1 pc



Features:

- Cuts a mortice for the body and face-plate
- Fast and accurate, saves you time and money
- Carbide wood cutters
- The self-centring jig cuts marking-up time
- Vertical guides, height and depth stops mean that you cannot overrun the cut area

E Housing kit

- Aluminium

Type, door thickness	Cat. No.
Standard, up to 55 mm	001.67.706

Order qty: 1 pc



F Shaft

- Screw-on shaft design
- Steel

Length	Depth of mortice cut	Cat. No.
Standard shaft		
220 mm	100 mm	001.67.742
Long shaft		
298 mm	180 mm	001.67.743

Order qty: 1 pc

G Spare depth stop

- Fits standard shaft and long shaft
- Steel

	Cat. No.
Depth stop	001.67.747

Order qty: 1 pc

H 6 x grub screws and allen key

- Spare grub screws and allen key for depth stop
- Steel

	Cat. No.
Grub screws and allen key	001.67.709

Order qty: 1 pc

TCH-FF 2010, HUK. Dimensional data not binding. We reserve the right to alter specifications without notice.