



A Double action pivot set, frame mounted

- Allows doors to swing in either direction
- Door plates radiused for easy preparation
- Bottom bracket is frame mounted
- For medium duty internal doors
- Minimum door thickness **44 mm**
- To suit doors up to **80 kg**, when bracket floor mounted
- Maximum door width **1100 mm**, when jamb mounted
- 44 mm thick doors require R9 radius on pivot edge, 54 mm thick doors require R12 radius
- Top and bottom plates have maintenance free oil impregnated bronze bearings
- Set includes door bottom pivot, top centre and Ø 5 mm screws to suit
- Maintenance free, guaranteed 25 years
- **Note:** It is recommended that both lock and hinge stiles are brush stripped for privacy.
- Stainless steel, grade 304

Finish	Cat. No.
Satin stainless steel	932.87.030

Order qty: 1 pc



B Steel double action pivot set, frame mounted

- Allows doors to swing in either direction
- Door plates radiused for easy preparation
- Bottom bracket is frame mounted
- For light duty internal doors
- Minimum door thickness **38 mm**
- To suit doors up to **20 kg**, when bracket floor mounted
- Maximum door width **950 mm**, when jamb mounted
- Maintenance free, guaranteed 25 years
- White powder coated mild steel

Finish	Cat. No.
White	932.87.057

Order qty: 1 pc



C 3D Adjustable hinge

- The 3D adjustable maintenance-free door hinge is developed for long-life performance under the most arduous conditions
- Tested to comply with Grade 11 BS EN 1935:2002 (80 kg for 200,000 cycles)
- Patented innovative design
- Independant adjustment in all three axes by 4 mm key ±2.5 mm height, ±2 mm side, ±2 mm depth (compression)
- No shims - all adjustments can be carried out in situ
- High resistance to corrosion
- Easy 3D adjustment
- Fixing screws included
- Supercoat 500 Silver / Yellow zinc

Height x width x depth	92 x 93 x 14/2.7 mm
Finish	
Silver	926.90.409
Gold	926.90.408

Order qty: 1 pc



D Stainless steel continuous hinge

- 1834 mm length
- Ideal for use on moveable door stops and lighter doors, where gaps would prove to be a hazzard
- Medium duty
- 36 holes per hinge
- Stainless steel, mill finish, stainless steel pin

Open width	Cat. No.
39 mm	351.13.000
51 mm	351.13.010

Order qty: 1 pc (1834 mm length)

