




**BS EN 179:2008**



**A Push pad emergency latch**

- The StarTec emergency exit latch is designed to comply with requirements of EN 179 for emergency exit applications:  
 Fire rated for timber and steel doors  
 Suitable for single doors and the active leaf (1st opening) of a rebated double door set
- 180 x 55 x 100 mm (height x width x depth)
- Suitable for doors up to 1300 mm wide
- Handed
- Tested and approved to **BS EN 179: 2008**, Emergency Exit Doors and is CE marked
- Fully fire tested to EN 1634-1 for use on timber and steel doors
- Low projection, category 1 - the hardware stands off the door no more than 100 mm - allowing the hardware to be used on any fire or escape door that will not open beyond 90°
- Can be used with accessories - rim cylinder, digital code lock, or outside access device, shown on page 27
- Supplied with cast universal latch striker
- The keep can be surface mounted or morticed into the frame for a single doors
- Fixings included

Finish	Left hand	Right hand
Silver powder coated	911.52.064	911.52.065

Order qty: 1 set

**EN 179 - Emergency Exit applications**

Where a final exit door is to be used only by trained personnel and where they are familiar with and have been shown a route to exit as an emergency exit door and must be certified to European Standard EN 179. The standard is intended for such areas as places of work which are not accessible to members of the public. Emergency Exit devices can be operated by push pads and lever handles.

**Other accessories available:**

Information on request

Item	Cat. No.
Easycode mechanical digital lock	912.06.278
Screw-in rim cylinder	916.90.710
Adapter for rim cylinder	911.52.066

**B Outside access device with lever and Euro profile cylinder**

- 175 x 146 x 80 mm (including lever)
- Suitable for use as outside access device for StarTec push bar panic latch and StarTec emergency push pad latch, shown on page 26
- Easily re-handed on site for right and left applications
- Supplied with a 40 mm single Euro profile cylinder, polished nickel
- Bolt through fixing from the inside for timber and metal doors upto 54 mm thick

Finish	Cat. No.
Silver	911.52.079

Order qty: 1 pair



**C Outside access device with knob and Euro profile cylinder**

- 175 x 55 x 88 mm (including knob)
- Suitable for use as outside access device for StarTec push bar panic latch and StarTec emergency push pad latch, shown on page 26
- Easily re-handed on site for right and left applications
- Supplied with a 40 mm single Euro profile cylinder, polished nickel
- Bolt through fixing from the inside for timber and metal doors upto 54 mm thick

Finish	Cat. No.
Silver	911.52.078

Order qty: 1 pair



TCH-FF 2010, HUK. Dimensional data not binding. We reserve the right to alter specifications without notice.