



A Intumescent strip, plain

- Fire seal only
- Self adhesive fixing
- Length 2.1 m

| Width x depth | White | Brown |
|--------------------|------------|------------|
| FD30 rating | | |
| 10 x 4 mm | 950.18.007 | 950.18.001 |
| 15 x 4 mm | 950.18.017 | 950.18.011 |
| FD60 rating | | |
| 20 x 4 mm | 950.18.027 | 950.18.021 |
| 25 x 4 mm | 950.18.037 | 950.18.031 |
| 30 x 4 mm | 950.18.047 | 950.18.041 |

Order qty: 1 pc



B Intumescent strip, with brush seal

- Fire and smoke seal
- Self adhesive fixing
- Length 2.1 m

| Width x depth | White | Brown |
|--------------------|------------|------------|
| FD30 rating | | |
| 10 x 4 mm | 950.18.107 | 950.18.101 |
| 15 x 4 mm | 950.18.117 | 950.18.111 |
| FD60 rating | | |
| 20 x 4 mm | 950.18.127 | 950.18.121 |
| 25 x 4 mm | 950.18.137 | 950.18.131 |
| 30 x 4 mm | 950.18.147 | 950.18.141 |

Order qty: 1 pc



C Flex n Seal weather strip

- Tested to BS 7386 class 1
- Suitable for inward opening doors and windows
- Fitting tolerance 5 mm
- Surface fixing
- Reversible blade - ideal for centre rail of sliding sash windows and double doors
- Set comprises 3 pcs seal and carrier:
 2x 2134 mm and 1x 914 mm lengths for 2 sides and 1 top of the door
- Aluminium carrier with black EPDM seal

| Width x height | Cat. No. |
|----------------|------------|
| 19 x 18 mm | 950.17.260 |

Order qty: 1 set



D Threshold seal, normal rating

- Suitable for hinged doors opening in and out
- Suitability: Industrial, commercial and public buildings, normal site conditions, forklift, wheelchair and trolleys, commercial and domestic vehicle
- Designed for use with panic bolts on emergency doors, 4 mm thick profiled upstand secures bottom shoot
- Low profile, 12 mm upstand
- Fitting tolerance, subject to installation
- Ends protected by weather deflecting end caps
- Fixing screws included
- Aluminium with EPDM seals

| Length x width | Cat. No. |
|----------------|------------|
| 1000 x 127 mm | 950.17.241 |
| 1828 x 127 mm | 950.17.242 |

Order qty: 1 pc

Item E.
 Catalogue shows 300 m
 Correct dimension is 2.1 m




E 'Aquamac 89' door seal

- Requires kerf slot 2.7 x 6 mm
- Recommended seal gap 5-13 mm
- Lifetime guarantee
- Conforms to BS 644
- BBA approved
- Abrasion resistant liner over sealing foam

| Length | White | Brown |
|--------|------------|------------|
| 2.1 m | 950.20.237 | 950.20.231 |

Order qty: 1 pc

Item F.
 Length dimension reverted
 back to 300 m as shown on
 original catalogue page



F 'Aquamac 63' door seal

- Requires kerf slot 2.7 x 6 mm
- Recommended seal gap 3.4-5.4 mm
- Lifetime guarantee
- Conforms to BS 644
- BBA approved
- Abrasion resistant liner over sealing foam

| Length | White | Brown |
|--------|------------|------------|
| 300 m | 950.20.207 | 950.20.201 |

Order qty: 1 pc

Item G.
 Catalogue shows 100 m
 Correct dimension is 125 m



G 'Aquamac 124' window seal

- Requires kerf slot 3.0 x 7 mm
- Recommended seal gap 5.0-7.3 mm
- Lifetime guarantee
- Conforms to BS 644
- BBA approved
- Abrasion resistant liner over sealing foam

| Length | White | Brown |
|--------|------------|------------|
| 125 m | 950.20.157 | 950.20.151 |

Order qty: 1 pc



H 'Aquamac 21' window seal

- Requires kerf slot 2.7 x 6 mm
- Recommended seal gap 5.0-7.5 mm
- Lifetime guarantee
- Conforms to BS 644
- BBA approved
- Abrasion resistant liner over sealing foam

| Length | White | Brown |
|--------|------------|------------|
| 250 m | 950.20.217 | 950.20.211 |

Order qty: 1 pc