StarTec Glass Door Fittings For Double Action Doors





A Bottom patch fitting for double action doors

- H x W x D: 51 x 162 x 31 mm
- For glass thickness 10-12 mm
- Max load bearing capacity 80 kg
- Max door width 1100 mm
- For left and right hand use
- With insert for flat conical floor spring pivot
- Concealed clamp fixing with hexagon socket head screws
- Adapter plate for 10 mm thick glass included
- Stainless steel covers

Finish	Cat. No.
Matt stainless steel	981.00.000
Polished stainless steel	981.00.001
Order atv: 1 pc	

Order qty: 1 pc



B Top patch fitting for double action doors

- H x W x D: 51 x 162 x 31 mm
- For glass thickness 10-12 mm
- Max load bearing capacity 80 kg
- Max door width 1100 mm
- For left and right hand use
- With plastic pivot insert for bolt Ø 15 mm
- Concealed clamp fixing with hexagon socket head screws included
- Adapter plate for 10 mm thick glass included
- · Stainless steel cover

Finish	Cat. No.
Matt stainless steel	981.00.010
Polished stainless steel	981.00.011
Order atv: 1 pc	

Order qty: 1 pc

CH-FF 2010, HUK. Dimensional data not binding. We reserve the right to alter specifications without notice.

C Ceiling bearing

- H x W x D: 2.5 (plate) x 106 x 28 mm
- Counter bearing for top patch fitting or top rail
- For screw fixing
- Stainless steel

FinishCat. No.Matt stainless steel981.00.080Order qty:1 pc



D Fanlight pivot patch fitting

- H x W x D: 51 x 162 x 31 mm, Ø 15 x 20 mm bearing
- For glass thickness 10-12 mm
- For left and right hand use
- Counter bearing for top path fitting or top rail

M8 threaded hole at rear for wall mounting

- Concealed clamp fixing with hexagon socket head screws
- Bolt can be adjusted laterally by +/- 3 mm
- Adaptor plate for 10 mm thick glass
 included
- Brass spreading dowel with M8 threaded bolt included
- Stainless steel covers

Finish	Cat. No.
Matt stainless steel	981.00.020
Polished stainless steel	981.00.021
Order gty: 1 pc	



E Fanlight pivot patch fitting

- H x W x D: 51 x 162 x 31 mm, Ø 15 x 20 mm bearing
- For glass thickness 10-12 mm
- For left and right hand use
- Counter bearing for top patch fitting or top
 rail

Screw-on plate at rear for wall mounting

- Concealed clamp fixing with hexagon socket head screws
- Bolt can be adjusted laterally by +/- 3 mm
- Adapter plate for 10 mm thick glass and screw-on plate included

Stainless steel covers

Finish	Cat. No.
Matt stainless steel	981.00.110
Polished stainless steel	981.00.111
Order qty: 1 pc	



F Fanlight/side panel pivot patch fitting

- H x W x D: 106 x 218 x 31, Ø 15 x 20 mm bearing
- For glass thickness 10-12 mm
- For left and right hand use
- Counter bearing for top patch fitting or top rail
- Concealed clamp fixing with hexagon socket head screws
- Bolt can be adjusted laterally by +/- 3 mm
- Adapter plate for 10 mm thick glass included
- Stainless steel covers

Finish	Cat. No.
Matt stainless steel	981.00.030
Polished stainless steel	981.00.031
Order gty: 1 pc	



G Fanlight/side panel connection patch fitting for single doors

- Hx W x D: 106 x 106 x 31 mm
- For glass thickness 10-12 mm
- For left and right hand use
- Concealed clamp fixing with hexagon socket head screws
- Adapter plate for 10 mm thick glass, mounting insert and 2 x dummy inserts for double action doors included

Stainless steel covers

Finish	Cat. No.
Matt stainless steel	981.00.060
Polished stainless steel	981.00.061
Order qty: 1 pc	

12

Sales and Support Head Office 01788 542 020 • Bristol 0117 935 9645 • Manchester 0161 745 8242 London 020 8551 8888 • Scotland 01698 422 525 • Wales 01269 831 433 • Yorkshire 01977 680 388

