# Glass Door Fittings - StarTec For Double Action Doors



Double Euro profile cylinders are shown on



### A Glass connection patch fitting

- H x W x D: 105 x 51 x 31 mm
- For glass thickness 10-12 mm
- For connecting 2 glass panes
- Without thread
- · Concealed clamp fixing with hexagon socket head screws
- Adapter plate for 10 mm thick glass and glass connecting patch fitting included
- Stainless steel covers

Finish	Cat. No.
Matt stainless steel	981.00.130
Polished stainless steel	981.00.131
Order atv: 1 pc	



# **B** Glass connection patch fitting

- H x W x D: 105 x 51 x 31 mm
- For glass thickness 10-12 mm
- For connecting 2 glass panes with glass to wall connection

#### With M8 thread

- Concealed clamp fixing with hexagon socket head screws
- Adapter plate for 10 mm thick glass and brass spreading dowel with M8 threaded bolt included
- · Stainless steel covers

Finish	Cat. No.
Matt stainless steel	981.00.140
Polished stainless steel	981.00.141
Order atv: 1 pc	A

0

Architectural Ironmongery

12



# C Glass connection patch fitting

- H x W x D: 106 x 106 x 31 mm
- For glass thickness 10-12 mm
- For connecting 2-4 glass panes · Concealed clamp fixing with hexagon
- socket head screws
- Adapter plate for 10 mm thick glass included

# • Stainless steel cover

Finish		Cat. No.
Matt s	ainless steel	981.00.120
Polishe	ed stainless steel	981.00.121
Order qt	y: 1 pc	

Double Euro profile cylinders are shown on page 18



#### **D** Patch lock with profile cylinder aperture

- H x W x D: 162 x 51 x 58 mm
- For glass thickness 10-12 mm
- For profile cylinder (31.5/31.5 mm)
- Deadbolt: 1 turn
- For left and right hand use
- Concealed clamp fixing with hexagon socket head screws
- Adapter plate for 10 mm thick glass and fixing screws for profile cylinder included

## • Stainless steel covers

Finish	Cat. No.
Matt stainless steel	981.00.410
Polished stainless steel	981.00.411
Order gty: 1 pc	



# **E** Centre strike patch for lock

- H x W x D: 162 x 51 x 31 mm
- For glass thickness 10-12 mm
- · For left and right hand use
- Concealed clamp fixing with hexagon • socket head screws
- Adapter plate for 10 mm thick glass included

# · Stainless steel covers

Finish	Cat. No.
Matt stainless steel	981.00.420
Polished stainless steel	981.00.421
Order qty: 1 pc	



page 18

### F Corner patch lock with profile cylinder aperture

- H x W x D: 51 x 162 x 58 mm
- For glass thickness 10-12 mm
- For profile cylinder (31.5/31.5 mm)
- Deadbolt: 1 turn
- · For left and right hand use
- · Concealed clamp fixing with hexagon socket head screws
- · Adapter plate for 10 mm thick glass, striking plate with fixing material and fixing screws for profile cylinder included

#### • Stainless steel covers

Finish	Cat. No.
Matt stainless steel	981.00.400
Polished stainless steel	981.00.401
Order qty: 1 pc	



#### G Overpanel strike patch for corner lock

- H x W x D: 51 x 162 x 31 mm
- For glass thickness 10-12 mm
- For DIN left hand and DIN right hand use
- · M8 threaded hole at rear for wall mounting
- Concealed clamp fixing with hexagon socket head screws
- Adapter plate for 10 mm thick glass and brass spreading dowel with M8 threaded bolt included

# Stainless steel covers

Finish	Cat. No.
Matt stainless steel	981.00.470
Polished stainless steel	981.00.471
Order qty: 1 pc	

