

System 4 = approx. Ø 100 mm (internal dimension)

System 5 = approx. Ø 125 mm (internal dimension)

System 6 = approx. Ø 150 mm (internal dimension)

Rigid pipe

- Recommended component for maximum airflow
- Flame retardant white PVC



System	Cat. No.
System 4	565.30.800
System 5	565.30.802
System 6	565.30.804

Order qty: 1 pc (1 pc = 1 m length)



System 5



Systems 4 and 6

Connector

- White flame retardant material
- To be used with rigid pipe 565.30.800/2/4

System	Cat. No.
System 4	565.30.600
System 5	565.30.900
System 6	565.30.602

Order qty: 1 pc

Round reducer

- Choice of three sizes:
 - System 5, suitable for many applications where a system 5 spigot or flange needs to be connected to a system 4 component
 - Suitable where approx. Ø 150 mm spigot needs to be connected to a system 5 component
 - Suitable where approx. Ø 125 mm spigot needs to be connected to a system 6 component
- Flame retardant white material

Please note:
These may be used as fan connectors, but may reduce airflow



System	Cat. No.
System 5 to 4	565.30.860
System 6 to 5	565.30.861

Order qty: 1 pc

90° Round pipe connector

- Flame retardant white material



System	Cat. No.
System 4	565.30.825
System 5	565.30.826
System 6	565.30.821

Order qty: 1 pc

System 4 = approx. Ø 100 mm (internal dimension)

System 5 = approx. Ø 125 mm (internal dimension)

System 6 = approx. Ø 150 mm (internal dimension)

Round pipe to flat duct convertor

- Connects flat ducts to components with round configuration such as wall vents and cooker hood spigots
- Can be connected to flexhose via threaded hose coupler
- Flame retardant white material



System	Cat. No.
System 4 to system 4a	565.30.780
System 5 to system 5a	565.30.782
System 6 to system 6a	565.30.784

Order qty: 1 pc

Flat duct

- Can be concealed behind cornice, in ceiling voids or cavity walls
- Connects to all rectangular component sockets
- Available in two lengths: 1 m and 1.5 m
- Flame retardant white PVC



Length	System 4a	System 5a	System 6a
1000 mm	565.30.730	565.30.732	565.30.734
1500 mm	565.30.731	565.30.733	565.30.735

Order qty: 1 pc (1 pc = 1 or 1.5 m length)

Flat duct connector

- Straight connector between two lengths of flat duct
- Flame retardant white material



System	Cat. No.
System 4a	565.30.740
System 5a	565.30.742
System 6a	565.30.744

Order qty: 1 pc

Horizontal 90° bend connector

- Connects two sections of flat duct at right angles - horizontal to horizontal
- Flame retardant white material



System	Cat. No.
System 4a	565.30.750
System 5a	565.30.752
System 6a	565.30.754

Order qty: 1 pc

Vertical 90° bend connector

- Connects two sections of flat duct at right angles - vertical to horizontal
- Flame retardant white material



System	Cat. No.
System 4a	565.30.760
System 5a	565.30.762
System 6a	565.30.764

Order qty: 1 pc

TCH-FF 2010, HUK. Dimensional data not binding. We reserve the right to alter specifications without notice.