



A Profile rod

- Standard length of 2.0 or 2.5 m
- Polished nickel-plated drawn steel
- Please ask for information on price and minimum order quantities of special cut to size lengths


Rod Ø	2.0 m	2.5 m
Ø 6 mm	226.07.209	226.07.254
Ø 8 mm	226.67.205	226.67.250

Order qty: 1 pc (2.0 or 2.5 m length)




Profile rod
Ø 6 mm

Profile rod
Ø 8 mm



Profile cross section
of catch hook




B Top and bottom catch hooks

- Screw fixing
- Polished nickel-plated zinc alloy with plastic guide

Rod Ø	Cat. No.
Ø 6 and Ø 8 mm	226.30.790

Order qty: 1 pair




C Rod guide, screw fixing

- Polished nickel-plated zinc alloy with plastic guide

Rod Ø	Cat. No.
Ø 6 mm	239.75.796
Ø 8 mm	239.75.798

Order qty: Multiples of 20 pcs





D Locking bolt

- With screw fixing plate
- Zinc alloy

Finish	Cat. No.
Polished nickel-plated	226.57.708

Order qty: Multiples of 20 pcs



E Fixed handle, screw mounting

- With M4 internal thread
- Zinc alloy
- **Accessories:** 1x M4 x 25 mm mounting screw

Finish	Cat. No.
Matt nickel-plated	229.81.600

Order qty: 1 pc




Fig. shows: 30 mm lock handle with 1.2 mm cover plate and lever cylinder core





Fig. shows: 30 mm lock handle with 4.2 mm cover plate and pin tumbler cylinder core



F Lock handle for cylinder cores

- For on-site installation of cylinder cores
- Left or right handed
- For 19 mm wood thickness
- Matt nickel-plated zinc alloy
- **Note:** It is only possible to remove the lock handle by using the release pin

Handed	Cat. No.
Left	229.80.620
Right	229.80.610

Order qty: 1 pc



G Release pin

- Plastic cap with steel pin

Release pin	Cat. No.
Release pin	229.85.990

Order qty: 1 pc

TCH-FF 2010, HUK. Dimensional data not binding. We reserve the right to alter specifications without notice.