# Minifix K.D. Connecting Fittings

## Minifix Standard Bolts with M4 Thread



- Minifix connecting bolts A with M4 thread are used in conjunction with sleeves or dowels for installation in Ø 5 mm, Ø 8 mm or Ø 10 mm pre-drilled holes
- For single or double-sided constructions




#### = Cross slot

Tighten with PZ2 screwdriver only (cross-slot size 2)



#### = Combination slot

Tighten with a PZ2 screwdriver or flat bladed screwdriver




#### A Connecting bolt

- With M4 thread for screwing into sleeves or dowels for installation in Ø 5 mm, Ø 8 mm or Ø 10 mm holes
- Plastic-coated, yellow chromatized steel

Drilling distance <b>B</b>	24 mm	34 mm
Cat. No.	262.27.458	262.28.455
0 1 1 14 11: 1	1 100	

Order qty: Multiples of 100 pcs





### B Sleeve, M4 internal thread

- For Ø 5 mm holes
- · Bright brass

Length	Cat. No.	
8 mm	051.45.004	

Order qty: Multiples of 100 pcs





## C Glued in sleeve, M4 internal thread

- For Ø 8 mm or Ø 10 mm holes
- With grooves for glue
- Natural-coloured nylon

Length	Ø 8 mm	Ø 10 mm
10 mm	039.33.042	039.33.239
13 mm	-	039.33.033

Order qty: Multiples of 100 pcs








## D Sleeve

- With M4 internal thread, for press-fit installation in Ø 5 mm holes
- Suitable for double-sided constructions
- Steel

Length	Bright	Galvanized
15 mm	267.00.011	267.00.911
18 mm	267.00.012	267.00.912
22 mm	267.00.013	267.00.913

Order qty: Multiples of 100 pcs





### E End screw, pan head

- With M4 thread and combination slot
- For screwing into sleeve **C** for single-sided constructions
- Drive: PZ2 cross slot
- Nickel-plated steel

Length	8 mm	10 mm
Cat. No.	020.92.711	020.92.720

Order qty: Multiples of 100 pcs

