


A M6 connecting screw, complete fitting

- Suitable for joining separate cabinets, for plinth frames/assemblies and many other purposes
- Plastic sleeve
- Plastic head element with galvanized steel threaded pin and screw-driver slot

| For wood thickness | Length | Brown | Beige | White |
|--------------------|----------|------------|------------|------------|
| 15-18 mm | 30-39 mm | 267.06.102 | 042.00.408 | 267.06.702 |

Order qty: Multiples of 100 pcs




B M6 Connecting screw, complete fitting

- Suitable for joining separate cabinets, for plinth frames/assemblies and many other purposes
- Plastic sleeve
- Plastic head element with galvanized steel threaded pin and screw-driver slot

| For wood thickness | Length | White | Brown |
|--------------------|--------|------------|------------|
| 36-45 mm | 34 mm | 267.06.723 | 267.06.123 |

Order qty: Multiples of 100 pcs




C M6 connecting screw, complete fitting

- All-metal. Comprising screw with steel threaded pin and screwdriver slot and milled sleeve without screwdriver slot
- Galvanized steel

| For wood thickness | Length | Cat. No. |
|--------------------|--------|------------|
| 34-41 mm | 29 mm | 267.07.902 |
| 37-44 mm | 32 mm | 267.07.903 |
| 40-48 mm | 36 mm | 267.07.904 |

Order qty: Multiples of 10 pcs

Re-instated **Discontinued** ●
Discontinued when stock = 0 +



D M6 connecting screw, complete fitting

- With combi slot for PZ2 cross slot or flat-bladed screwdrivers
- Steel

| For wood thickness | Length | Nickel-plated | Black | Burnished steel |
|--------------------|--------|---------------|------------|-----------------|
| 32-42 mm | 15 mm | 267.05.702 | - | 267.05.102 |
| 36-46 mm | 20 mm | 267.05.703 | 267.05.303 | ● 267.05.103 |
| 46-56 mm | 30 mm | 267.05.704 | - | 267.05.104 |
| 56-66 mm | 40 mm | 267.05.705 | - | - |
| 66-76 mm | 50 mm | 267.05.706 | - | - |


Order qty: Multiples of 100 pcs

13.07.10/1



E M6 sleeve nut

- Two versions: Milled, without screwdriver slot or not milled, with screwdriver slot
- Galvanized steel




| Version | Cat. No. |
|-----------------------------------|------------|
| Milled, without screwdriver slot | 267.07.910 |
| Not milled, with screwdriver slot | 267.07.911 |

Order qty: Multiples of 100 pcs

F Threaded sleeve, M4 internal thread

- For use with M4 connecting screw G
- Countersunk head
- With combi slot for PZ2 cross slot or flat-bladed screwdrivers
- Nickel-plated steel




| For wood thickness | Length | Cat. No. |
|--------------------|--------|------------|
| 28-36 mm | 27 mm | 267.01.715 |
| 37-45 mm | 35 mm | 267.01.717 |

Order qty: Multiples of 100 pcs


G Connecting screw, M4 thread

- For use with M4 threaded sleeve F
- Countersunk head
- With combi slot for PZ2 cross slot or flat-bladed screwdrivers
- Nickel-plated steel




| Length | Cat. No. |
|--------|------------|
| 15 mm | 022.34.157 |

Order qty: Multiples of 100 pcs



H Sleeve, M4 internal thread

- For use with M4 end screw G
- For press-fit installation in Ø 5 mm holes
- Suitable for double-sided constructions
- Galvanized steel




| For wood thickness | Length | Cat. No. |
|--------------------|--------|------------|
| 24-26 mm | 15 mm | 267.00.911 |
| 24-29 mm | 18 mm | 267.00.912 |
| 28-33 mm | 22 mm | 267.00.913 |
| 36-40 mm | 30 mm | 267.00.916 |

Order qty: Multiples of 100 pcs

I End screw, M4 thread

- For screwing into sleeve H for single-sided constructions
- Pan head
- With combi slot for PZ2 cross slot or flat-bladed screwdrivers
- Nickel-plated steel



| Length | Cat. No. |
|--------|------------|
| 8 mm | 020.92.711 |
| 10 mm | 020.92.720 |

Order qty: Multiples of 100 pcs