## Connecting Fittings

# **Keku Push-In Fittings**


Notice: Supporting plastic fittings may not be treated with chemical solvent or aggressive greases!

Makrolon has a temperature stability from -100° C to + 135° C

Hospa and Varianta screws are








### A Panel component AS

- Screw fixing with Hospa or Varianta screws
- Black Makrolon
- Frame component to be ordered separately

Mounting with	Cat. No.
Hospa screws	262.50.359
Varianta screws	262.50.358

Order qty: Multiples of 50 pcs




### B Spacer plate for panel component A

Black polycarbonate

Mounting with	Cat. No.
Hospa screws	262.50.352
Varianta screws	262.50.354

Order qty: Multiples of 50 pcs



# C Frame component AS

- Screw fixing with Hospa or Varianta screws
- Black Makrolon

TCH-FF 2010, HUK. Dimensional data not binding. We reserve the right to after specifications without notice.

Mounting with	Cat. No.
Hospa screws	262.50.368
Varianta screws	262.50.377

Order qty: Multiples of 50 pcs


#### Packed sets

- Push fit fasteners
- Packed sets include panel and frame component

Packed set	Cat. No.
<b>A</b> 262.50.359 + <b>C</b> 262.50.368	262.50.313
<b>A</b> 262.50.359 + <b>C</b> 262.50.377	262.50.322


ixconnect | HAFEI

Order qty: Multiples of 50 sets









### **□** Frame component ASR

- Screw fixing with Hospa or Varianta screws
- Black Makrolon

Mounting with	Cat. No.
Hospa screws	262.50.390
Varianta screws	262.50.391

Order qty: Multiples of 50 pcs





Thread Ø 6.0




### E Hospa chipboard screw, countersunk head

Galvanized steel

Length	Cat. No.
15 mm	015.31.826
17 mm	015.31.835
20 mm	015.31.844

Order qty: Multiples of 1000 pcs



### F Varianta screw, countersunk head

- For Ø 3 mm or Ø 5 mm hole
- Steel

Length	Hole Ø 3 mm	Hole Ø 5 mm
	Galvanized	Nickel-plated
10.5 mm	013.15.617	013.05.719
13.5 mm	013.15.626	340.29.724
16.0 mm	013.15.635	013.15.733

Order qty: Multiples of 100 pcs

(0)