

Flap Fittings

Lid Stays with Adjustable Braking

Duo Forte 3666 lid stay

- **Heavy version** - min. installation depth **175 mm**
- Opening angles: **75°, 90°, 110°**
- Unhanded design
- For use with wooden lids or lids with aluminium frames, also suitable for use as flap stay
- For flaps with aluminium frame with frame width 20 mm or from 45 mm
- With braking and locking mechanisms, can be adjusted using an **SW4** hex key
- Self closing function
- Clip-mounting on pre-mounted screw fixing brackets, no tools required
- Height ± 2 mm, side $+3/-1$ mm, tilt ± 1.5 mm and pull adjustment facility
- Nickel-plated steel bracket
- Nickel-plated zinc alloy lid stay
- Installation instructions included

Headings added

For wooden lids/lids with aluminium frame width from 45 mm

Distance from edge	Cat. No.
28 mm	373.66.631
37 mm	373.66.632

For lids with aluminium frame width 20 mm

Distance from edge	Cat. No.
28 mm	373.66.641
37 mm	373.66.642

Order qty: 1 pc



Table showing maximum flap weight

Flap height	Maximum flap weight (kg)			
	Function locking		Function braking	
	1 stay	2 stays	1 stay	2 stays
For opening angle 75°				
200	14.0	15.0	15.0	15.0
250	11.5	15.0	15.0	15.0
300	9.0	15.0	12.0	15.0
350	8.0	15.0	11.0	15.0
400	7.0	14.0	9.0	15.0
450	6.0	12.5	8.0	15.0
500	5.5	11.0	7.0	15.0
550	5.0	10.0	6.5	13.0
600	5.0	9.5	6.0	12.0
650	4.0	8.5	5.5	11.0
700	4.0	8.0	5.0	10.5
For opening angle 90°				
200	12.0	15.0	15.0	15.0
250	9.5	15.0	12.0	15.0
300	8.0	15.0	10.0	15.0
350	7.0	13.5	9.0	15.0
400	6.0	12.0	8.0	15.0
450	5.0	11.0	7.0	14.0
500	5.0	9.5	6.0	12.0
550	4.0	8.5	5.5	11.0
600	4.0	8.0	5.0	10.0
650	3.5	7.0	5.0	9.5
700	3.0	7.0	4.0	9.0
For opening angle 110°				
200	9.5	15.0	12.5	15.0
250	7.5	15.0	10.0	15.0
300	6.5	12.5	8.0	15.0
350	5.5	11.0	7.0	14.0
400	4.5	9.5	6.0	12.5
450	4.0	8.5	5.5	11.0
500	4.0	7.5	5.0	10.0
550	3.5	7.0	4.0	9.0
600	3.0	6.0	4.0	8.0
650	3.0	5.5	4.0	7.5
700	3.0	5.0	3.5	7.0



C Duo 3667 and Duo forte 3666 lid stays

- Opening angle 75°, 90° and 110°
- With self closing function
- For left and right hand use
- Clips onto pre-mounted mounting bracket
- Locks in any position, locks in end position to brake, released by slight pressure
- Includes fitting instructions
- Nickel plated zinc alloy

Model series	Cat. No.
Duo	373.66.660
Duo forte	373.66.661

Order qty: 1 set

Item C.
Catalogue shows...
'1 pc'
Correct order qty is **'1 set'**



D Mounting bracket

- For use with **Duo 3667** and **Duo forte 3666**
- For mounting the lid stay to the cabinet
- Nickel plated steel

	Cat. No.
For edge distance (cabinet) 28 mm	373.66.693
For edge distance (cabinet) 37 mm	373.66.694

Order qty: 1 pc



For wooden flaps or flaps with aluminium frame, from frame width 45 mm



For flaps with aluminium frame, frame width 20 mm

E Screw-on bracket

- For mounting the lid stay to the flap
- Nickel plated steel

	Cat. No.
For wooden flaps or flaps with aluminium frame, from frame width 45 mm	373.66.681
For flaps with aluminium frame, frame width 20 mm	373.66.682

Order qty: 1 pc

23.08.10/2*