
- · Screw or dowel fixing cup

- Slide on arm
- · Semi concealed, specially designed for fold back doors
- Nickel-plated zinc alloy cup and arm
- Mounting plates for slide on hinges are shown on page 23-24
- Hinge arm cover plates are shown on page **25**





Slide on

rew fixing			
1-21 mm			
23.23.612			
For door thickness 15-18 mm			
23.23.603			

Ø 35 mm cup			
Crank 0	Dowel fixing	Screw fixing	
For door thickness		14-21 mm	
	323.31.610	323.31.600	

Order qty: Multiples of 10 pcs

Mounting screws

• Hospa chipboard screws raised head, Nickel-plated steel, Ø 3.5 mm with cross slots




Length	Cat. No.	Order qty
15 mm	015.55.639	1000
17 mm	015.55.648	1000
20 mm	015.55.657	1000

Screw fixing **Dowel fixing**






Ø 30 mm cup




Ø 35 mm cup



ss b	b
55	-


HAFELE

0 Crank









Full overlay


-X

• Opening angle 180°

- 0 mm crank, with catch
- Ø 35 mm cup
- · Screw fixing cup

Correct page number is

- Slide on arm
- Semi concealed, for rebated doors
- Antique brass zinc alloy cup and arm
- Straight mounting plates for use with this hinge are shown on page 22
- Hinge arm cover plates are shown on page **25**
- Please note: Hinge subject to colour variations due to manufacturing process used






Slide on


Finish	Screw fixing
For door thickness	14-21 mm
Antique brass	343.30.106

Screw fixing





0 Crank





Drawing shows mounting plate thickness f = 2

Order qty: Multiples of 10 pcs