



Overlay e	6	7	8
DBE	4	5	6

A Mini hinge

- For **overlay** doors
- Opening angle **92°**
- Sprung
- Ø 26 mm cup
- Screw fixing
- Nickel-plated stamped steel cup and nickel-plated zinc alloy arm
- **Spacer plates** must be ordered separately if required

	Cat. No.
Mini hinge	361.73.500

Order qty: 1 pc



B Spacer plate

- When spacer plate is used door overlay is reduced by **2 mm**
- Nickel-plated steel
- **Spacer plates must be ordered separately**

	Cat. No.
Spacer plate	361.72.022

Order qty: Multiples of 10 pcs

Mounting screws

Hospa chipboard screws raised head Ø 3.5 mm with cross slots



Length	Cat. No.
15 mm	015.55.639
17 mm	015.55.648
20 mm	015.55.657

Order qty: Multiples of 1000 pcs

Door buffers and cover caps are shown on pages 41-42



Door buffer B, page 41, Cat. No. 356.24.705



Door buffer E, page 41, Cat. No. 356.20.707



Door buffer H, page 41, Cat. No. 356.19.940



Cover cap D, page 42, Cat. No. 340.44.700

TCH-FF 2010, HUK. Dimensional data not binding. We reserve the right to alter specifications without notice.