# **Twin Wheel Castors**



Important note: Unless otherwise indicated fixing screws are not included and must be ordered separately.

The symbol shown next to the drawing indicates the type and size of screw required.

Fixing materials can be found in Section 11 from page 3.



## A Twin wheel castor, plate fixing, hooded

- With 38 x 38 mm mounting plate
- 25 x 25 screw hole distances
- · Without brake
- Matt black plastic

Wheel Ø/ Static capacity	Height/Width	Cat. No.
Ø 35/25 kg	48/38 mm	660.07.301

Order qty: 1 pc



### B Twin wheel castor, plate fixing, hooded

- With 42 x 42 mm mounting plate
- 32 x 32 screw hole distances
- · Without brake

TCH-FF 2010, HUK. Dimensional data not binding. We reserve the right to after specifications without notice.

Matt black plastic

Wheel Ø/ Static capacity	Height/Width	Cat. No.	
Ø 40/35 kg	54/38 mm	660.07.311	

Order qty: 1 pc

#### All suitable for use on soft floor covering such as carpet.



#### C Twin wheel castor, M8 thread fixing, hooded

- With M8 x 15 mm threaded bolt
- For use with M8 T-nuts
- Without brake
- · Matt black plastic

Wheel Ø/ Static capacity	Height/Width	Cat. No.	
Ø 35/25 kg	45/38 mm	660.07.304	
Ø 40/35 kg	50/40 mm	660.07.314	

Order qty: 1 pc



Galvanized finish



M8 T-nuts, knock-in

- With four prongs
- For use in mounting M8 thread fixing castors under wooden bases
- Steel

Finish	Ø	Cat. No.
Dull	Ø 9.5 mm	031.00.285
Galvanized	Ø 9.5 mm	031.00.481

Order qty: Multiples of 100 pcs