


A M10 plinth adjusting screw

- Slot in screw tip provides simple adjustment of plinth height using a screwdriver
- For use with **C, D, E, F** or **G**
- Bright galvanized steel

Length	Cat. No.
60 mm	637.02.009
69 mm	637.02.018
80 mm	637.02.027
90 mm	637.02.036
100 mm	637.02.045
120 mm	637.02.054

Order qty: 1 pc





B Protective cap

- Press fits onto baseplate of **A**
- Transparent plastic

Cat. No.
Protective cap

637.02.090

Order qty: Multiples of 100 pcs





C Screw on bracket

- Galvanized steel

Cat. No.
Screw on bracket

637.07.004

Order qty: 1 pc






D Screw on bracket

- Galvanized steel

Cat. No.
Screw on bracket

637.06.007

Order qty: 1 pc





E Screw on plate

- Galvanized steel

Cat. No.
Screw on plate

637.09.008

Order qty: 1 pc





F Screw in socket

- With screwdriver slot
- With M10 internal thread
- Bright steel

Cat. No.
Screw in socket

030.00.502

Order qty: 1 pc



G M10 T-nut, knock-in

- With four prongs
- Dull steel

Cat. No.
M10 T-nut

031.00.301

Order qty: Multiples of 100 pcs