

Fittings for Pivot Sliding Cabinet Doors

Accuride 1432, Vertical Use

Accuride 1432 pivot sliding door runners



- For vertical use
- For panel thickness **19-32 mm** on inset door
- For panel thickness **19 mm** on overlay doors
- Maximum door weight **34 kg**
- Door panel width **254-660 mm**
- Door panel height **914-2300 mm**
- Cable system for synchronised slide operation
- Order hinges and carrier strip set separately
- Black zinc-plated steel

Installed length	Extension length	Dim. A	Dim. B	Cat. No.
303 mm	210 mm	-	256.5	408.24.530
354 mm	261 mm	-	307.3	408.24.535
405 mm	312 mm	-	358.1	408.24.541
456 mm	343 mm	177.5	408.9	408.24.546
506 mm	394 mm	202.9	459.7	408.24.551
557 mm	445 mm	228.3	510.5	408.24.556
608 mm	496 mm	253.7	561.3	408.24.561
659 mm	546 mm	279.1	612.1	408.24.566
710 mm	597 mm	304.5	662.9	408.24.571

Order qty: 1 pair (per door)

Item	Cat. No.
Hinge carrier strip set	408.24.090
Extra connector clip set	408.24.091
35 mm hinge set for inset doors	408.24.092
40 mm hinge set for overlay doors	408.24.093
40 mm hinge set for thick inset doors	408.24.094

Order qty: 1 pairs

Hinge ordering guide		
Door panel height	No. of hinges required	No. of sets required
914 - 1193 mm	3	2 sets (discard 1 hinge)
1194 - 1498 mm	4	2 sets
1499 - 1803 mm	5	3 sets (discard 1 hinge)
1804 - 2000 mm	6	3 sets
2001 - 2300 mm	6	3 sets

Order qty: 1 pairs

Hinge carrier strip ordering guide	
Door panel height	No. of 408.24.090 required
914 - 1422 mm for 1 door	1 set
914 - 1422 mm for 2 doors	2 sets
1423 - 2000 mm for 1 door	2 sets (discard 1 strip)
1423 - 2000 mm for 2 doors	3 sets
2001 - 2300 mm for 1 door	2 sets
2001 - 2300 mm for 2 doors	4 sets

Order qty: 1 pairs

