

Fittings for Straight Sliding Timber Cabinet Doors

HAWA-Planfront 220 for Flush Finish Doors



Supplementary fittings for straight sliding side panels - Side panels can be accommodated as straight sliding doors, operating on HAWA-Junior 40 top track with certain components from HAWA-Dorado Infront 2-door fitting set, **providing side panels do not exceed 40 kg.**

Please note: Side panels between 40 and 80 kg can be accommodated on application.

Please contact the Architectural Ironmongery department for further information




HAWA-Planfront 220

Plan of upper track layout



Plan of bottom guide channel layout



E Top track

With screw holes for soffit fixing. Silver anodised aluminium

Length	2.0 m
Cat. No.	940.80.200

Order qty: 1 pc (2.0 m length)

F Trolley hanger

M10, with sleeve bearing mounted, high-grade polyamide tandem rollers

Cat. No.	940.80.012
----------	------------

Order qty: 1 pc (order 2 pcs per door)

G Suspension unit

With M10 hanger bolt, for use with hanger F. Nickel-plated zinc alloy

Cat. No.	940.81.020
----------	------------

Order qty: 1 pc (order 2 pcs per door)

H Track stopper

For adjustable mounting in top track. Zinc-alloy, **black painted**, housing with steel spring and rubber buffer.

Cat. No.	940.80.041
----------	------------

Order qty: 1 pc

I Lower guide profile

Press-fits into groove in underside of door, brown plastic

Length	3.0 m
Cat. No.	406.73.103

Order qty: 1 pc (3.0 m length)

J Bottom guide, clear threshold

Plug fits into floor. Silver anodised aluminium

Cat. No.	407.01.990
----------	------------

Order qty: 1 pc (order 2 pcs per door)

K Espagnolette lock

Rim-type, double-locking. **5-pin levers** provide 20,000 possible different key changes. Accessories include: 2 keys and cylinder rosette. Steel case and brass cylinder; matt nickel-plated

Handed	Left	Right
Cat. No.	231.45.655	231.45.600

Order qty: 1 pc (order 1 pc per door - handed)

L Profile rod

For use with lock K. Zinc plated steel, solid profile

For approx. 2000 mm high doors

Order qty: 1 pair = 2x 975 mm lengths	
Cat. No.	239.81.930

For approx. 2500 mm high doors

Order qty: 1 pair = 1x 975 mm, 1x 1475 mm length	
Cat. No.	239.81.950

Order qty: 1 pair (order 1 pair per door)

M Rod guide

For use with lock K. Polished nickel-plated steel

Cat. No.	239.68.014
----------	------------

Order qty: 1 pc (order 5 pcs per door)

N Rod striking-plate

For use with lock K. Press-fit type. Polished nickel-plated steel

Finish	Cat. No.
White	239.60.750
Brown	● 239.60.152

Order qty: 1 pc (order 2 pcs per door)

Item H.
Text added

Item H.
Illustration amended

Discontinued ●
Discontinued when stock = 0 +

Door with groove 6 x 13 mm

