

- Application: Top hung system for wardrobes, cupboards and similar doors. Single or multiple runs of track. Heavy-duty use
- Range: Max. door weight 45 kg Max. door height 2.1 m Max. door width 1.2 m

• Recommended door construction

Door thickness: 20-40 mm

Door frame width: Min. 38 mm to accommodate hanger aprons

Door width: Quarter height minimum

- Fixing: Top track soffit fixed. Individual tracks allow for variation of door thickness. Guides at floor level recessed or surface fixed. On triple track installations floor channel **G** together with bottom guides F should be used as shown below. Position hangers close to edge of doors Sets are supplied with fixing materials
- Complete fitting sets are available for two or three doors. Single door fitting set also available for when another door is added.
- Hanger B can be supplied separately if required

Twin 100 complete fitting sets

- A Top track. Drilled for soffit fixing. 1.8 and 2.4 m lengths when supplied in packed sets. 2.4 m length only when supplied separately. Aluminium
- B Rear hanger. Back fixing. Nylon wheels, ground steel axles, plated steel adjustable aprons
- C Front hanger. Back fixing. Nylon wheels, ground steel axles, plated steel adjustable aprons
- D Door stop. Nylon with rubber buffer
- E Bottom guide. Wood screw fixing. Nylon used in pairs

Twin 100 complete sets

TWIII 100 COMplete Sets						
Fitti	ng sets fo	or	2 doors	3 doors		
A Top track			2 lengths	2 lengths		
B Rear hanger C Front hanger D Door stop E Bottom guide		2 pcs	2 pcs			
		2 pcs	4 pcs			
		1 pc	2 pcs			
		4 pcs	6 pcs			
Set	Door	or Track Cat. N		No.		
	opening	length	2 doors	3 doors		
6 H	1.8 m	1.8 m	407.19.239			
8 H	2.4 m	2.4 m	-	407.19.328		

Single door fitting set

olligic door litting set	
For additional door	
C Front hanger	2 pcs
D Door stop	1 pc
E Bottom guide	2 pcs
Set	Cat. No.
1 H	407.19.006

Order qty: 1 set

Additional top track, 2.4 m length

04:110:

Order qty: 1 pc (2.4 m length)

B Additional rear hanger

Cat. No.	407.19.9	38
Order qty:	1 pair (order 1 pair per door)	

F Bottom guide

Steel plate with nylon blade

otoo, plato III	array to the blade	
Cat. No.		409.12.990

Order qty: 1 pc (order 2 pcs per door)

G Guide channel

10

Pre-drilled for countersunk screws. Bright aluminium

	00011101001111 00101101	Brigin alaminan
Length	2.1 m	3.0 m
Cat. No.	409.14.010	409.14.029

Order qty: 1 pc (2.1 or 3.0 m length)

H Bottom guide, heavier duty


For where a more robust guide is preferred, clear threshold. Black plastic

Ca	at. No.			940	.40.031
_					

Order qty: 1 pc (order 1 pc per door)





Two doors on double track




Three doors on double track


Door	Dim x		
thickness			
20 mm	2 mm		
22 mm	4 mm		
25 mm	7 mm		
30 mm	12 mm		
32 mm	14 mm		
35 mm	17 mm		
40 mm	22 mm		




















Optional guiding systems for extra robustness or triple track installations:

These must be ordered in addition to the complete set











For ancillary door hardware i.e. locks, handles and bolts etc. refer to page 19