


- Application:** Inset doors only - double, parallel or single run. Light duty glass doors - for high quality work  
**Clipo 15 GR** with complete aluminium frame profile surround. Cut profile to mitre, assemble with corner connecting mounting brackets and fasten with screws

**Clipo 15 GKK** with glass surround profile glued top and bottom only


- Range:** Max. door weight **10/15 kg**  
 Max. door width **800 mm**  
 Max. door height **1200 mm**

**Clipo 15 GR** for glass thickness **4 mm**, max. glass weight **10 kg**  
 Frame profile length = width of glass door + 23 mm

**Clipo 15 GKK** for glass thickness **6 mm**  
 Frame profile length = width of glass door + 6 mm



Top track groove mounted  
 No groove in floor  
 Without fascia  
 With concealed running gear






### A Double top track (alternative)

With screw holes for soffit fixing. For 25 mm thick upper carcass. Bright aluminium

Length	2.5 m	3.5 m
Cat. No.	405.90.010	405.90.020

Order qty: 1 pc (2.5 or 3.5 m length)






### B Double top track (alternative)

With swivel lug soffit fixing at 100 mm intervals. For min. 19 mm thick upper carcass. **Not suitable for hardwood.** Bright aluminium

Length	2.5 m	3.5 m
Cat. No.	405.89.017	405.89.026

Order qty: 1 pc (2.5 or 3.5 m length)



### C Aluminium frame profile

Glue to glass. Silver anodised aluminium

Length	2.5 m	3.5 m
Cat. No.	405.78.925	405.78.935


Order qty: 1 pc (2.5 or 3.5 m length)

### D End buffer profile, GR



Edge fits glass frame profile. Light grey plastic

Length	2.5 m
Cat. No.	405.77.525

Order qty: 1 pc (2.5 m length)



### Clipo 15 GR




### E Glass fixing profile, GR

Clip on. Grey plastic

Length	2.5 m
Cat. No.	401.65.525

Order qty: 1 pc (2.5 m length)



**Drilling jig 405.08.000** available to cut profile to insert running gear

### F Rhodia 3B Silicon, 310 ml tube

For gluing glass to aluminium frame profile

Cat. No.	405.54.020
----------	------------

Order qty: 1 pc (order 1 pc per pair of doors)

### Clipo 15 GR and 15 GKK fitting sets

**G Track stopper.** For top tracks, with retaining spring. Grey plastic

**H Running gear, GR.** Light grey plastic. Vertical adjustment  $\pm 1$  mm. **Drilling jig 405.08.000** available to cut profile to insert running gear

**I Mounting component.** To locate GR running gear. Fixes inside glass frame profile using allen key. Grey plastic

**J Mounting bracket, GR.** For assembly of glass frame profile, using allen key. Yellow chromated steel

**K Running gear, GKK.** Anthracite plastic. Vertical adjustment  $\pm 1$  mm.

**L End cap, GKK.** For frame profile. With mounting screw. Anthracite plastic

**M Bottom guide.** Press fit. Anthracite plastic

For 2 doors	15 GR	15 GKK
G Track stopper	4 pcs	4 pcs
H GR Running gear	4 pcs	-
I GR Mounting component	4 pcs	-
J GR Mounting bracket	8 pcs	-
K GKK Running gear	-	4 pcs
L GKK End cap	-	4 pcs
M Bottom guide	2 pcs	2 pcs
Cat. No.	405.82.261	405.82.282

Order qty: 1 set (order 1 set per pair of doors)

