

Fittings for Straight Sliding Timber Interior Doors

HAWA-Junior 80/B Low Headroom

- **Application:** Vertically adjustable sliding door fitting for low and restricted headroom applications. Tandem rollers made of high-grade polyamide, mounted in an aluminium carriage, ensure exceptionally light and silent action. All parts are corrosion resistant
- **Range:** Max. door weight **80 kg**
Min. door thickness **35 mm**
Max. door height normally **2.3 m**
- **Tracks are not included in the fitting set and must be ordered separately**
- Installation drawing reference **17689**



For ancillary door fittings, locks, handles, bolts, seals, etc. see pages 4-6

A Junior 80 top track

With screw-holes for soffit fixing. Silver anodised aluminium

Length	Cat. No.
2.0 m	940.80.200
2.5 m	940.80.250
3.0 m	940.80.300

Order qty: 1 pc (2.0, 2.5 or 3.0 m length)

Junior 80/B fitting set

B Trolley hanger. Sleeve bearing mounted, high-grade polyamide, tandem rollers. Retainer profile with suspension plate. **M10** hanger pendant and tension bolt. Complete with fastening materials

C Locking wrench. For suspension profile

D Profile plugs. Grey plastic

E Track stopper. For adjustable mounting in top track. Zinc alloy, **black painted**, housing with steel spring and rubber buffer. Adjustable retaining force

F Guide, rattle proof. For screw mounting to floor. Black plastic

G Rubber buffer. Screw fixing

For 1 door	
B Trolley hanger	2 pcs
C Locking wrench	1 pc
D Profile plugs	2 pcs
E Track stopper	1 pc
F Guide	1 pc
G Rubber buffer	1 pc
Cat. No.	940.80.002

Order qty: 1 set

Important mounting note: If the sliding door is required to stop at both ends, we recommend installing an additional track stopper **E**

E Additional track stopper

Cat. No.	940.80.041
----------	------------

Order qty: 1 pc

H Assembly wedge

For insertion in trolley hanger retainer profile. Allows trolley hangers to be fixed from the side edge of the panel, when the top track and the top of the door is inset into the ceiling, making fixing from the front impossible. Allows installation and removal of doors without disassembling door linings and channels.

Aluminium

Cat. No.	940.80.050
----------	------------

Order qty: 1 set (2 pcs)

Item I and J: Alternative light duty guiding with continuous aluminium channel:

I Guide. Light duty. Steel plate with nylon blade

Cat. No.	409.12.990
----------	------------

Order qty: 1 pc (2 pcs required per door)

J Channel

Pre-drilled for countersunk screws. Bright aluminium

Length	2.1 m	3.0 m
Cat. No.	409.14.010	409.14.029

Order qty: 1 pc (2.1 or 3.0 m length)

