Application: Straight sliding metal doors or **curved** track applications for straight or **curved** metal doors. For **external applications** exposed tracks may require protective coating (by others)

· Range:

Max. door weight 250 kg Min. door thickness 35 mm

Precision radius curves over 1 metre radius can be provided to order. Curved 'track systems' will require special consideration, contact Technical Support for further information

Important: Please state whether tracks must be curved open side out or in

• Installation drawing reference 14586

For ancillary door fittings, locks, handles, bolts, etc. see pages 4-6

A Top track, side fixing

Stainless steel grade 304. For large applications track can be butt jointed

Length	Cat. No.
3.0 m	942.42.301

Order qty: 1 pc (3.0 m length)

B Top track, soffit fixing

With top mounting flanges at approx. 500 mm intervals. Stainless steel grade 304

Length	Cat. No.
3.0 m	942.43.301

Order qty: 1 pc (3.0 m length)

C Trolley hanger

Galvanized steel trolley with tandem ball bearing mounted steel rollers

Cat. No.	942.44.012
Order qty:	1 pc (2 pcs required per panel)

Mounting plate

With M12 hanger bolt and fixing screws. Galvanized

Cat. No.				942.44.026
			/0	

Order qty: 1 pc (2 pcs required per panel)

E Bolt on track stopper

May be placed in pairs for extra strength. With two black rubber buffers. Galvanized steel

Cat.	No.		942.42.041	

Order qty: 1 pc (4 pcs required per panel)

F Rubber buffer

Screw fixing

TOH-AI 2008, HUK. Dimensional data not binding. We reserve the right to after specifications without notice.

	Cat	. No.			S	941.60.051	
_			-	10		p.	

Order qty: 1 pc (2 pcs required per panel)

G Bottom guide channel

Fixed to underside of panel. $20 \times 20 \text{ mm}$.

Pre-drilled for countersunk screws. Silver anodised aluminium

alaminam	
Length	Cat. No.
2.5 m	940.41.250
3.5 m	940.41.350

Order qty: 1 pc (2.5 or 3.5 m length)

H Guide

For screw mounting to floor, clear threshold applications only. Grey plastic

Cat. No.	942.44.030

Order qty: 1 pc (1 pc required per panel)



















