

**BS EN 12209 2** (0-4) **F** A-G) •B# kg B 6 2 **4** 1-9) **0** (0) 2

24 84 Item B. Text amend B Mortice cylinder escape sashlock case Operation: Latchbolt and deadbolt operated by ╘ lever handles inside. Deadbolt operated by cylinder outside, latchbolt operated by lever 0 235 0[] 15 Case: Black coated steel, 15 mm wide 72 Λ Forend: Square, 2 piece. Stainless steel or brass Strike plate: Square. Flat. Stainless steel or brass. Splinter guard included 00 Latch bolt: Stainless steel. Reversible Deadbolt: Stainless steel. 15 mm throw 0 Follower: 8 mm. Suitable for both sprung and Backset unsprung furniture. Split follower. Gripping 55 Holed for bolt through furniture at 38 mm centres 29 25 0 Fixing instructions and template included 198 Order cylinders separately; see pages 40-50 Requires split spindle 909.83.711 to operate,



Refer to pages 2-3 for information on BS EN 12209,

lock grades and classification

165

0


0

18

Rebate sets for these locks are shown on page 12

17.11.08/1\*

0 180



•

.

handle outside

feature

55 mm backset

Section 1 Finish

Polished brass

Order qty: 1 pc

Satin stainless steel

Fixing screws included

refer to Section 1, page 63 for details

For lever handles and escutcheons refer to

Cat. No.

911.55.130

911.55.131



2

Refer to pages 2-3 for information on BS EN 12209,

130