Hinge A has obtained Certifire approval.

Clockwise closing Maintenance free, 25 year performance guarantee. hinge

Anti-clockwise closing = Right hand hinge

Refer to pages 2-3 for information on BS EN 1935, hinge grades and classification

A Loadmaster stainless steel butt hinge


- ANSI hole pattern (template drilled)
- Grade **14** BS EN 1935


Fixings for timber included.

- Maximum adjusted door weight 160 kg
- Minimum door thickness 44 mm
- Square and radius corners
- Maintenance free oilite bush bearings
- 25 year performance guarantee
- Certifire approved; certificate no. CF351 30 mins
- Ø 5.5 x 30 mm wood screws included
- Grade 316 stainless steel

Length x width	102 x 89 mm	
Finish	Satin	Polished
Square corners	926.91.120	926.91.121
Radius corners	926.91.300	926.91.301

Order qty: 1 pc










Satin stainless steel finish shown Square corners

B Loadmaster stainless steel butt hinge

- ANSI hole pattern (template drilled)
- Maximum adjusted door weight 200 kg
- Minimum door thickness 44 mm
- Square and radius corners
- Maintenance free oilite bush bearings
- 25 year performance guarantee
- Ø 5.5 x 30 mm wood screws included
- Grade 316 stainless steel

Length x width	114 x 114 mm	
Finish	Satin	Polished
Square corners	926.91.130	926.91.131
Radius corners	926.91.310	926.91.311

Order qty: 1 pc





Satin stainless steel finish shown Square corners

C Loadmaster stainless steel lift-off hinge

- ANSI hole pattern (template drilled)
- Maximum adjusted door weight 120 kg
- Minimum door thickness 44 mm
- Square and radius corners
- Maintenance free oilite bush bearings
- 25 year performance guarantee
- Ø 5.5 x 30 mm wood screws included
- Grade 316 stainless steel

Length x width	102 x 89 mm	
Square corners	Satin	Polished
Clockwise closing	926.91.320	926.91.321
Anti-clockwise cl.	926.91.322	926.91.323
Radius corners	Satin	Polished
Clockwise closing	926.91.330	926.91.331
Anti-clockwise cl.	926.91.332	926.91.333

Order qty: 1 pc

\bigoplus \bigcirc \bigoplus 102 \bigcirc \bigcirc Ø 16



Satin stainless steel finish shown Anti-clockwise closing Square corners

Variants available to order, subject to quantity:

Staggered hole pattern

Dog bolt (fixed pin only)

Conductor (fixed pin only)


Anti-ligature

Also available in mild steel.



Staggered hole pattern







TCH-AI 2008, HUK. Dimensional data not binding. We reserve the right to alter specifications without notice.

Anti-ligature