

**Item A.**  
Photo amended



**A 'Fire door keep shut' mandatory sign**

- Ø 76 mm x 2 mm thick
- White on blue silk screened
- Drilled and countersunk
- Fixing screws included
- Conforms to BS 5499 pt.5:2002
- Aluminium, stainless steel or brass

Finish	Cat. No.
Polished anodised aluminium	987.01.621
Satin stainless steel	987.02.020
Polished stainless steel	987.02.021
Polished brass	987.01.828

Order qty: 1 pc



**B 'Fire door keep locked' mandatory sign**

- Ø 76 mm x 2 mm thick
- White on blue silk screened
- Drilled and countersunk
- Fixing screws included
- Conforms to BS 5499 pt.5:2002
- Aluminium, stainless steel or brass

Finish	Cat. No.
Polished anodised aluminium	987.01.631
Satin stainless steel	987.02.030
Polished stainless steel	987.02.031
Polished brass	987.01.838

Order qty: 1 pc



**C 'This door to be kept locked shut when not in use' mandatory sign**

- Ø 76 mm x 2 mm thick
- White on blue silk screened
- Drilled and countersunk
- Fixing screws included
- Conforms to BS 5499 pt.5:2002
- Aluminium, stainless steel or brass

Finish	Cat. No.
Polished anodised aluminium	987.16.009
Satin stainless steel	987.16.000
Polished stainless steel	987.16.001
Polished brass	987.16.008

Order qty: 1 pc



**D 'Automatic fire door keep clear' mandatory sign**

- Ø 76 mm x 2 mm thick
- White on blue silk screened
- Drilled and countersunk
- Fixing screws included
- Conforms to BS 5499 pt.5:2002
- Aluminium, stainless steel or brass

Finish	Cat. No.
Polished anodised aluminium	987.16.109
Satin stainless steel	987.16.100
Polished stainless steel	987.16.101
Polished brass	987.16.108

Order qty: 1 pc



**E 'Fire door keep locked shut' mandatory sign**

- Ø 76 mm x 2 mm thick
- White on blue silk screened
- Drilled and countersunk
- Fixing screws included
- Conforms to BS 5499 pt.5:2002
- Aluminium, stainless steel or brass

Finish	Cat. No.
Polished anodised aluminium	987.16.129
Satin stainless steel	987.16.120
Polished stainless steel	987.16.121
Polished brass	987.16.128

Order qty: 1 pc



**F 'Fire door keep clear' mandatory sign**

- Ø 76 mm x 2 mm thick
- White on blue silk screened
- Drilled and countersunk
- Fixing screws included
- Conforms to BS 5499 pt.5:2002
- Aluminium, stainless steel or brass

Finish	Cat. No.
Polished anodised aluminium	987.16.139
Satin stainless steel	987.16.130
Polished stainless steel	987.16.131
Polished brass	987.16.138

Order qty: 1 pc



**G 'Fire escape keep clear' mandatory sign**

- Ø 76 mm x 2 mm thick
- White on blue silk screened
- Drilled and countersunk
- Fixing screws included
- Conforms to BS 5499 pt.5:2002
- Aluminium, stainless steel or brass

Finish	Cat. No.
Polished anodised aluminium	987.16.149
Satin stainless steel	987.16.140
Polished stainless steel	987.16.141
Polished brass	987.16.148

Order qty: 1 pc

For further information on **BS 5499**, please refer to the Standards pages shown at the back of this catalogue

TCH-A1 2008, HUK. Dimensional data not binding. We reserve the right to alter specifications without notice.

20.01.09/1\*