

# Fittings to Aid Disabled Persons

## Door Solutions - Pocket Hideaway Door System

### Pocket Hideaway door system

#### • Application:

Internal straight sliding door gear primarily for domestic housing applications.

With Building Regulations Part M approval, the system is particularly suitable for use by physically challenged people, and is ideal for dining rooms, ensuite bathrooms, cloakrooms and doors into kitchens

Providing an efficient, economical way of allowing increased space and easier access, the "pocket door" concept enables sliding doors to become a significant design feature of a home

#### • Range -

Max. door weight	56 kg
Max. door height	2032 mm
Max. door width	1067 mm
Door thickness	28-50* mm

\*For 44-50 mm door thickness use cavity widening set J

#### • Pocket Hideaway complete set

comprises header assembly with pre-fitted track A and fittings B, C, D, E, F and G

#### • For bi-parting doors use 2 sets and 1 Hideaway jointing fitting set I

#### • Sets are supplied complete with fixing materials and installation instructions

**A Header assembly**, with pre-fitted track marked in increments for easy cutting down where narrower doors are required.

**B Steel wrapped timber studs**. Provides stability and helps to prevent nails used for fixing plasterboard from protruding and scratching the door panel

**C Hangers**, with 3 wheels. Steel mounting plate with nylon rollers. Quick release clip for easy removal from fixing plate

**D Floor plates**. Steel

**E Bottom guides**. Nylon

**F Door stop**. Rubber

**G Frame adaptor fitting set**. For 35-44 mm door thickness. Comprises 4 nylon spacers and 2 steel base plates

#### For 1 door

<b>A</b> Header assembly	1 pc
<b>B</b> Steel wrapped studs	1 set
<b>C</b> Hangers	2 pcs
<b>D</b> Floor plates	2 pcs
<b>E</b> Bottom guides	2 pcs
<b>F</b> Door stop	1 pc
<b>G</b> Frame adaptor set	1 set
Max. door width	Cat. No.
760 mm	940.58.005
915 mm	940.58.006
1067 mm	940.58.007

Order qty: 1 set

#### **H** Pocket door flip up handle

For use with cavity sliding doors. Brass

Finish	Cat. No.
Satin nickel	911.26.078
Satin brass	911.26.079

Order qty: 1 pc

#### **I** Jointing fitting set.

For use with 2 Pocket Hideaway door sets fitted side by side to make bi-parting doors

Cat. No.	940.58.020
----------	------------

Order qty: 1 set

#### **J** Cavity widening set.

For use when door thickness is between 44-50 mm - increases cavity width to 62 mm. Plywood spacers are pre-cut for use with 1067 mm wide door, cut down for narrower doors. Comprises 2 pcs base plate

Cat. No.	940.58.030
----------	------------

Order qty: 1 set

For other types of handle refer to **Section 2** page 85 and **Section 4** pages 75-82

