



## A Drilling jig

- For mounting Dialock DTSH door terminals on wooden doors
- Using the drilling jig:**  
Align drilling jig with stop parallel to door edge and fix with suitable screw clamp  
Drill required holes into door using the drilling jig (at a right angle to door panel)  
Do not drill through the door panel - use drilling jig on both sides
- Drilling dimensions:**  
3 x  $\varnothing$  18 mm continuous  
1 x  $\varnothing$  16 mm continuous  
1 x  $\varnothing$  8 mm drilling for cable up to lock recess (only with logging of emergency opening)  
1 x  $\varnothing$  25 mm routing on the outside, min. 7 mm deep  
1 x  $\varnothing$  32 mm additional routing on the outside up to lock recess (only with logging of emergency opening)

Cat. No. 917.90.003

Order qty: 1 pc

## B Drill bit, $\varnothing$ 16 mm

- For drilling through-hole for leading cables through wooden doors

Cat. No. 910.54.994

Order qty: 1 pc

## C Router bit, $\varnothing$ 25 mm

- For through-hole to lock nut on wooden doors
- With reducing sleeve and centering pin

Cat. No. 910.54.995

Order qty: 1 pc

## D Router bit, $\varnothing$ 32 mm

- For widening the cable drilling on the outside through to the lock recess (only when logging the emergency opening)
- With centering pin

Cat. No. 910.54.997

Order qty: 1 pc

## E Spacer

- For use with thinner door panels
- Dimensions: 210 x 54 x 3 mm
- Not for use on fire resistant and smoke control doors
- Black ABS plastic

Cat. No. 917.90.490

Order qty: 1 pc



## F Fixing materials

- Comprises:  
1x 8 mm lever handle spindle  
4x M4 threaded screws
- Yellow galvanized steel spindle and galvanized steel screws

For door panel thickness	Spindle length	Thread length of screw	Cat. No.
37-47 mm	100 mm	50 mm	917.90.410
47-57 mm	110 mm	60 mm	917.90.411

Order qty: 1 set



## G Maintenance tool

- For Dialock DTSH door terminals
- For unscrewing the inner cover (required for battery change)
- To remove the cap on the external module for emergency opening with a profile cylinder
- With built-in magnet
- Using the maintenance tool:**  
After unscrewing the cover ring you can remove the inner cover, the battery hold then becomes accessible, and you can change the batteries  
With the magnet you can remove the cap on the external module - In an emergency you can then open the door with the built-in profile cylinder for a forced entry
- Bright aluminium

Cat. No. 917.90.031

Order qty: 1 pc



## H Batteries

- Alkaline manganese, 1.5 Volt type E91 (AA)
- 4 pcs required per DTSH door terminal

Cat. No. 910.54.980

Order qty: Multiples of 4 pcs

## I Pliers for retaining ring

- To unclip retaining ring
- For fitting lever handle spindle, as required

Cat. No. 917.90.900

Order qty: 1 pc

